

Specification

|                |         |
|----------------|---------|
| Stock No       | 854430  |
| Type           | REACH   |
| Make           | BT      |
| Model          | RRE160  |
| Year           | 2012    |
| Euromast       | 3F850   |
| Hours          | 15177   |
| Capacity       | 1600 kg |
| Lift height    | 8500    |
| Values         |         |
| Quality Rating | 3       |

Mechanical

|                                 |             |
|---------------------------------|-------------|
| Character.                      |             |
| Load Centre (c)                 | 600-1250 mm |
| Operating mode (Characteristic) | Seated      |

Weights

|                                |         |
|--------------------------------|---------|
| Service weight (Total weight ) | 4226 kg |
|--------------------------------|---------|

Wheels

|            |              |
|------------|--------------|
| Tyres type | Polyurethane |
|------------|--------------|

Dimensions

|                                       |                |
|---------------------------------------|----------------|
| Free lift (h2)                        | 2930 mm        |
| Lift height (h3)                      | 8500 mm        |
| Height of overhead guard (cabin) (h6) | 2200 mm        |
| Height of reach legs (h8)             | 300 mm         |
| Overall length (l1)                   | 2470 mm        |
| Length to fork face (l2)              | 1270 mm        |
| Overall width (b1/b2)                 | 1280 mm        |
| Forks length (l)                      | 1200-2000 mm   |
| Fork carriage (class)                 | DIN 15173 / 2A |
| Fork carriage width (b3)              | 1100 mm        |
| Fork spread (min/max) (b5)            | 870-260 mm     |
| Width between legs (b4)               | 900 mm         |
| Reach travel (l4)                     | 460 mm         |
| Ground clearance, mast (m1)           | 55 mm          |
| Length of chasis (l7)                 | 1750 mm        |
| Collapsed height (h1)                 | 3520 mm        |
| Forks width (e)                       | 130 mm         |

Performance

|               |                    |
|---------------|--------------------|
| Service brake | hydraulic/electric |
|---------------|--------------------|

Drive

|                          |                  |
|--------------------------|------------------|
| Battery weight           | 1235 kg          |
| Battery voltage/capacity | 48V / 620Ah V/Ah |
| Battery (Acc. to DIN)    | MIDAC            |

Attachment

|                                   |                                        |
|-----------------------------------|----------------------------------------|
| Attachments (Has attachment)      | Fork Positioners, Sideshift and Forks. |
| Attachment type (Attachment type) | Fork positioners, shaft guided         |

Engine

|                           |          |
|---------------------------|----------|
| Engine type (Engine type) | electric |
|---------------------------|----------|

Opinion

Location

Extras

|             |                                                                  |
|-------------|------------------------------------------------------------------|
| Extras      | SS, Fork Positioners, 6th Hydraulic, Hydraulic Extending Forks.. |
| Extras Hyds | 3rd, 4th & 5th                                                   |

Visual

Battery

|                                            |      |
|--------------------------------------------|------|
| Battery Year (Battery Year of Manufacture) | 2012 |
|--------------------------------------------|------|



**Appearance:** Very good cosmetic condition,  
**Mechanical Status:** Good working condition Battery 2014.11  
**More:** [Click here for more photos](#)

