

Specification

| | |
|----------------|---------|
| Stock No | 321522 |
| Type | DIESEL |
| Make | LINDE |
| Model | H40D-02 |
| Year | 2015 |
| Euromast | 2F313 |
| Hours | 1585 |
| Capacity | 4000 kg |
| Lift height | 3130 |
| Values | 3 |
| Quality Rating | 3 |

Mechanical

| | |
|---------------------------------|------------|
| Character. | |
| Load Centre (c) | 500/600 mm |
| Operating mode (Characteristic) | Seated |
| Wheelbase (y) | 1998 mm |

Weights

| | |
|----------------------------------|--------------|
| Service weight (Total weight) | 5985 kg |
| Axle load with load (front/rear) | 8610/1180 kg |

Wheels

| | |
|-------------------------|----------------|
| Tyres type | Superelastic |
| Tyres front condition | 45% |
| Tyres rear condition | 10% |
| Tyre size front | 250-15-SC15 mm |
| Tyre size rear | 250-15-SC15 mm |
| Track width front (b10) | 1221 mm |
| Track width rear (b11) | 1122 mm |

Dimensions

| | |
|--------------------------------------------|----------------|
| Lift height (h3) | 3130 mm |
| Extended height (h4) | 3750 mm |
| Height of overhead guard (cabin) (h6) | 2400 mm |
| Overall length (l1) | 4200 mm |
| Length to fork face (l2) | 3000 mm |
| Overall width (b1/b2) | 1446 mm |
| Forks length (l) | 1200 mm |
| Fork carriage (class) | DIN 15173 / 3A |
| Fork carriage width (b3) | 1745 mm |
| Ground clearance, mast (m1) | 158 mm |
| Ground clearance, centre of wheelbase (m2) | 201 mm |
| Turning radius (Wa) | 2672 mm |
| Ast across 1000x1200 (Ast) | 4355 mm |
| Ast along 800x1200 (Ast) | 4555 mm |
| Towing coupling height (h10) | 703 mm |
| Collapsed height (h1) | 2400 mm |
| Seat/stand height (h7) | 1226 mm |
| Forks height (s) | 50 mm |
| Forks width (e) | 120 mm |

Performance

| | |
|---------------------------------------------------|---------------|
| Travel speed (With, w/o load) | 21 km/h |
| Lifting speed (With, w/o load) | 0.53/0.56 m/s |
| Lowering speed (With, w/o load) | 0.52/0.57 m/s |
| Climbing ability (30 min rating - with, w/o load) | 29/34 % |
| Acceleration time (With, w/o load) | 5.5/4.8 sec |
| Service brake | hydrostatic |

Drive

| | |
|-----------------------------|----------|
| Drive motor (60 min rating) | 55 kW |
| Battery voltage/capacity | 12V V/Ah |

Other

| | |
|----------------------------|--------------------------|
| Noise level | 79 dB |
| Working pressure | 170 bar |
| Oil flow (For attachments) | 48 l/min |
| Traction control | HYDROSTATIC TRANSMISSION |

Attachment

| | |
|-----------------------------------|--------|
| Attachments (Has attachment) | Forks. |
| Attachment type (Attachment type) | Forks |

Engine

| | |
|-------------------------------|-----------|
| Manufacturer of engine/type | VW / AUDI |
| Engine rated power (ISO 1585) | 53 kW |
| Rated rpm | 2800 rpm |
| Cylinders/Displac. ccm | 4/1896 |
| Fuel consumption (VDI) | 4.6 l/h |
| Engine type (Engine type) | diesel |

Opinion

Location

Extras

| | |
|-------------|-----------------------------------------------------------------------------------------|
| Extras | Wide Carriage, Weigh Scales, Front and Rear Screen, LED Lights, Lightweight Tube Doors. |
| Extras Hyds | 3rd |

Visual



Appearance: Very good appearance for age.

Mechanical Status: Very good working order

More: [Click here for more photos](#)

