

Specification

	327990
	DIESEL
LINDE	
	H25D-02 392
	2016
	3F471
	10897
	2500 kg
	4710
	3
	4
	500 mm
	Seated
	3705 kg
	Superelastic
	Superelastic 60%
	LINDE

Dimensions	
Lift height (h3)	4710 mm
Extended height (h4)	4520 mm
Height of overhead guard (cabin) (h6)	2150 mm
Overall length (I1)	3640 mm
Length to fork face (I2)	2640 mm
Overall width (b1/b2)	1200 mm
Forks length (I)	1000 mm
Fork carriage (class)	DIN 15173 / 2A
Fork carriage width (b3)	1080 mm
Length of chasis (I7)	2550 mm
Collapsed height (h1)	2120 mm
Forks height (s)	40 mm
Forks width (e)	80 mm
Auxiliary lift (h9)	1610 mm
Performance	
Service brake	hydrostatic
Drive	
Drive motor (60 min rating)	30 kW
Battery voltage/capacity	12V V/Ah

Sideshift and Forks.

Sideshifts

VW / AUDI

4 cylinder


SS, LED Lights.

3rd

30 kW

diesel





More: Click here for more photos









Phone: Email: Website: +44(0) 1784 818181 sales@phl.co.uk https://www.phl.co.uk

Visual

Attachment

Engine

Opinion

Location

Extras

Extras Extras Hyds

Attachments (Has attachment)

Manufacturer of engine/type

Cylinders/Displac. ccm

Engine type (Engine type)

Engine rated power (ISO 1585)

Attachment type (Attachment type)