

Specification

|                |          |
|----------------|----------|
| Stock No       | 357786   |
| Type           | REACH    |
| Make           | LINDE    |
| Model          | R14S 115 |
| Year           | 2006     |
| Euromast       | 3F695    |
| Hours          | 4293     |
| Capacity       | 1400 kg  |
| Lift height    | 6950     |
| Values         |          |
| Quality Rating | 0        |

Mechanical

|                                 |                |
|---------------------------------|----------------|
| Character.                      |                |
| Load Centre (c)                 | 600/500/400 mm |
| Operating mode (Characteristic) | Seated         |
| Wheelbase (y)                   | 1275 mm        |
| Load distance (x)               | 311 mm         |

Weights

|                                  |              |
|----------------------------------|--------------|
| Service weight (Total weight )   | 3395 kg      |
| Axle load with load (front/rear) | 1800/1090 kg |

Wheels

|                                |              |
|--------------------------------|--------------|
| Tyres type                     | Polyurethane |
| Tyre size front                | 285 x 100 mm |
| Tyre size rear                 | 343 x135 mm  |
| Track width rear (b11)         | 1150 mm      |
| Wheels (front/rear (x=driven)) | 1x/2         |

Dimensions

|  |                |
|--|----------------|
| Mast or fork carriage tilt (alpha,beta)    | 2/4 grad       |
| Lift height (h3)                           | 6950 mm        |
| Extended height (h4)                       | 7570 mm        |
| Height of overhead guard (cabin) (h6)      | 2110 mm        |
| Height of reach legs (h8)                  | 310 mm         |
| Overall length (l1)                        | 2384 mm        |
| Length to fork face (l2)                   | 1184 mm        |
| Overall width (b1/b2)                      | 1234/1250 mm   |
| Forks length (l)                           | 1000 mm        |
| Fork carriage (class)                      | DIN 15173 / 2A |
| Fork carriage width (b3)                   | 830 mm         |
| Fork spread (min/max) (b5)                 | 296/690 mm     |
| Width between legs (b4)                    | 922 mm         |
| Reach travel (l4)                          | 425 mm         |
| Ground clearance, mast (m1)                | 75 mm          |
| Ground clearance, centre of wheelbase (m2) | 75 mm          |
| Turning radius (Wa)                        | 1540 mm        |
| Length of chassis (l7)                     | 1638 mm        |
| Ast across 1000x1200 (Ast)                 | 2655 mm        |
| Ast along 800x1200 (Ast)                   | 2715 mm        |
| Collapsed height (h1)                      | 2900 mm        |
| Seat/stand height (h7)                     | 940/1030 mm    |
| Forks height (s)                           | 40 mm          |
| Forks width (e)                            | 80 mm          |

Performance

|   |                 |
|---|-----------------|
| Travel speed (With, w/o load)                     | 13.5/13.5 km/h  |
| Lifting speed (With, w/o load)                    | 0.34/0.6 m/s    |
| Lowering speed (With, w/o load)                   | 0.55/0.45 m/s   |
| Climbing ability (30 min rating - with, w/o load) | 4.5/8.2 %       |
| Maximum climbing (With, w/o load)                 | 10/10 %         |
| Acceleration time (With, w/o load)                | 5.5/4.8 sec     |
| Service brake                                     | electromagnetic |

Drive

|                             |                  |
|-----------------------------|------------------|
| Battery weight              | 1196 kg          |
| Drive motor (60 min rating) | 6.5 kW           |
| Lift motor (15% rating)     | 12 kW            |
| Battery class               | British Standard |
| Battery voltage/capacity    | 48V / 775Ah V/Ah |
| Battery (Acc. to DIN)       | HOPPECKE         |

Other

|                            |           |
|----------------------------|-----------|
| Noise level                | 63 dB     |
| Working pressure           | 200 bar   |
| Oil flow (For attachments) | 6.5 l/min |

Attachment

|                                   |                      |
|-----------------------------------|----------------------|
| Attachments (Has attachment)      | Sideshift and Forks. |
| Attachment type (Attachment type) | Sideshifts           |

Engine

|                           |          |
|---------------------------|----------|
| Engine type (Engine type) | electric |
|---------------------------|----------|

Opinion

Location

Extras

|             |           |
|-------------|-----------|
| Extras      | SS.       |
| Extras Hyds | 3rd & 4th |

Visual

|  |               |
|--|---------------|
| Battery                                    |               |
| Battery Serial No                          | LB 1167088 U6 |
| Battery Year (Battery Year of Manufacture) | 2006          |



**Appearance:** Very good appearance for age

**Mechanical Status:** Very good working order

**More:** [Click here for more photos](#)

