

Specification

Stock No		357338
Туре		REACH
Make	LINDE	ne/ter
Model	LINDE	R20G-01 1120
Year		2015
Euromast		3F521
Hours		5386
Capacity		2000 kg
Lift height		5210
Values		5210
Quality Rating		3
Mechanical		
Character.		
Load Centre (c)		400-600 mm
Operating mode (Characteristic)		400-000 mm Seated
		Jealed
Weights		
Service weight (Total weight)		3700 kg
Wheels		
Tyres type		Superelastic
Dimensions		
Dimensions Free lift (h2)		1830 mm
Free lift (h2)		
		5210 mm
Free lift (h2) Lift height (h3)		5210 mm 2220 mm
Free lift (h2) Lift height (h3) Height of overhead guard (cabin) (h6) Height of reach legs (h8)		5210 mm 2220 mm 470 mm
Free lift (h2) Lift height (h3) Height of overhead guard (cabin) (h6) Height of reach legs (h8) Overall length (l1)		5210 mm 2220 mm 470 mm 2550 mm
Free lift (h2) Lift height (h3) Height of overhead guard (cabin) (h6) Height of reach legs (h8) Overall length (l1) Length to fork face (l2)		5210 mm 2220 mm 470 mm 2550 mm 1400 mm
Free lift (h2) Lift height (h3) Height of overhead guard (cabin) (h6) Height of reach legs (h8) Overall length (l1) Length to fork face (l2) Overall width (b1/b2)		5210 mm 2220 mm 470 mm 2550 mm 1400 mm 1470 mm
Free lift (h2) Lift height (h3) Height of overhead guard (cabin) (h6) Height of reach legs (h8) Overall length (l1) Length to fork face (l2) Overall width (b1/b2) Forks length (l)		5210 mm 2220 mm 470 mm 2550 mm 1400 mm 1470 mm 1150 mm
Free lift (h2) Lift height (h3) Height of overhead guard (cabin) (h6) Height of reach legs (h8) Overall length (l1) Length to fork face (l2) Overall width (b1/b2) Forks length (l) Fork carriage (class)		5210 mm 2220 mm 470 mm 2550 mm 1400 mm 1470 mm 1150 mm ISO / 28
Free lift (h2) Lift height (h3) Height of overhead guard (cabin) (h6) Height of reach legs (h8) Overall length (l1) Length to fork face (l2) Overall width (b1/b2) Forks length (l) Fork carriage (class) Fork carriage width (b3)		5210 mm 2220 mm 470 mm 2550 mm 1400 mm 1470 mm 1150 mm ISO / 2E 800 mm
Free lift (h2) Lift height (h3) Height of overhead guard (cabin) (h6) Height of reach legs (h8) Overall length (l1) Length to fork face (l2) Overall width (b1/b2) Forks length (l) Fork carriage (class) Fork carriage width (b3) Width between legs (b4)		5210 mm 2220 mm 470 mm 2550 mm 1400 mm 1470 mm 1150 mm ISO / 2E 800 mm 920 mm
Free lift (h2) Lift height (h3) Height of overhead guard (cabin) (h6) Height of reach legs (h8) Overall length (l1) Length to fork face (l2) Overall width (b1/b2) Forks length (l) Fork carriage (class) Fork carriage width (b3) Width between legs (b4) Reach travel (l4)		1830 mm 5210 mm 2220 mm 2550 mm 1400 mm 1470 mm 1150 mm ISO / 2E 800 mm 920 mm 710 mm
Free lift (h2) Lift height (h3) Height of overhead guard (cabin) (h6) Height of reach legs (h8) Overall length (l1) Length to fork face (l2) Overall width (b1/b2) Forks length (l) Fork carriage (class) Fork carriage width (b3) Width between legs (b4)		5210 mm 2220 mm 470 mm 2550 mm 1400 mm 1470 mm 1150 mm ISO / 2E 800 mm 920 mm
Free lift (h2) Lift height (h3) Height of overhead guard (cabin) (h6) Height of reach legs (h8) Overall length (l1) Length to fork face (l2) Overall width (b1/b2) Forks length (l) Fork carriage (class) Fork carriage width (b3) Width between legs (b4) Reach travel (l4)		5210 mm 2220 mm 470 mm 2550 mm 1400 mm 1470 mm 1150 mm 150 / 2E 800 mm 920 mm 710 mm

Drive	
Battery weight	1103 kg
Battery class	British Standard
Battery voltage/capacity	48v/775Ah V/Ah
Battery (Acc. to DIN)	HOPPECKE
Engine	
Engine type (Engine type)	electric
Opinion	

Location

Extras

Extras

SS,LIGHTS,DOOR,



Battery	
Battery Serial No	H00500002329
Battery Year (Battery Year of Manufacture)	08/2015



+44(0) 1784 818181 sales@phl.co.uk https://www.phl.co.uk



Appearance: Good Appearance for age. Mechanical Status: Good working condition More: Click here for more photos







